

POWERBOAT

The power of freedom



+38 0977 00 85 58

powerboatofficial@gmail.com

powerboat_official

powerboat.best



Passenger capacity	4 persons
Maximum load capacity	390 kg
Weight without engine	210 kg
Deadrise at transom	8°
Deadrise midships	11°
Immersion	180 mm
Length	4.2 m
Width	1.84 m
Permissible engine power	25-40 h.p.
Fuel tank capacity	mobile
Transom height	508 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm

STANDARD EQUIPMENT

- Marine grade deck covering (carpet/vinyl)
- Bow locker with two lids with coamings.
- Locker lighting
- Onboard lockers (2 pcs) for rods 2.6 m and 2.2 m long each
- Plastic locker handles (stainless optional)
- Bilge pump
- Aft/bow battery compartment
- Captain's and passenger's seats



Passenger capacity	4 persons
Maximum load capacity	460 kg
Weight without engine	580 kg
Deadrise at transom	12°
Deadrise midships	18°
Immersion	320 mm
Length	4.75 m
Width	2.09 m
Permissible engine power	60-115 h.p.
Fuel tank capacity	75 L
Transom height	508 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm

STANDARD EQUIPMENT

- Stationary fuel tank 75 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2 m and 2.5 m long each
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats



Passenger capacity	4 persons
Maximum load capacity	460 kg
Weight without engine	630 kg
Deadrise at transom	12°
Deadrise midships	18°
Immersion	320 mm
Length	4.75 m
Width	2.09 m
Permissible engine power	60-115 h.p.
Fuel tank capacity	75 L
Transom height	508 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm

STANDARD EQUIPMENT

- Stationary fuel tank 75 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2 m and 2.5 m long each
- Captain and passenger consoles
- Tempered windshield glass
- The door between the consoles
- Bow locker with two lids with coamings
- Lockers under the stern seats
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats
- Marine grade deck covering (carpet/vinyl)
- On-board navigation lights
- Folding aft seats
- On-board navigation lights
- Steering wheel with steering gear and cable
- A locker between the aft seats



POWERBOAT

470 SC



Passenger capacity	4 persons
Maximum load capacity	460 kg
Weight without engine	630 kg
Deadrise at transom	12°
Deadrise midships	18°
Immersion	320 mm
Length	4.75 m
Width	2.09 m
Permissible engine power	60-115 h.p.
Fuel tank capacity	75 L
Transom height	508 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm

STANDARD EQUIPMENT

- Stationary fuel tank 75 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2 m and 2.5 m long each
- Captain's console
- A locker between the aft seats
- Bow locker with two lids with coamings
- Lockers under the stern seats
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats
- Marine grade deck covering (carpet/vinyl)
- On-board navigation lights
- Folding aft seats
- Steering wheel with steering gear and cable



POWERBOAT

620 DC



Passenger capacity	5 persons
Maximum load capacity	710 kg
Weight without engine	750 kg
Deadrise at transom	14°
Deadrise midships	20°
Immersion	320 mm
Length	5.28 m
Width	2.28 m
Permissible engine power	90-150 h.p.
Fuel tank capacity	95 L
Transom height	508/635 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm

STANDARD EQUIPMENT

- Stationary fuel tank 95 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2.7 m long each
- Captain and passenger consoles
- Tempered wind glazing
- The door between the consoles
- Bow locker with two lids with coamings
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats
- Marine grade deck covering (carpet/vinyl)
- On-board navigation lights
- Folding aft seats (3 pcs)
- Chests under the aft seats
- Steering wheel



STANDARD EQUIPMENT

- Stationary fuel tank 95 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2.7 m long each
- Captain's console
- Chests under the aft seats
- Steering wheel
- Bow locker with two lids with coamings
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats
- Marine grade deck covering (carpet/vinyl)
- On-board navigation lights
- Folding aft seats (3 pcs)



Passenger capacity	5 persons
Maximum load capacity	710 kg
Weight without engine	720 kg
Deadrise at transom	14°
Deadrise midships	20°
Immersion	320 mm
Length	5.28 m
Width	2.28 m
Permissible engine power	90-150 h.p.
Fuel tank capacity	95 L
Transom height	508/635 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm



STANDARD EQUIPMENT

- Stationary fuel tank 95 l
- Aft locker for tent
- Locker lighting
- On-board lockers (2 pcs) for rods 2.7 m long each
- Steering wheel
- Stainless handles of lockers
- Bilge pump
- Battery locker on the cockpit deck
- Captain's and passenger's seats
- Marine grade deck covering (carpet/vinyl)
- Bow locker with two lids with coamings



Passenger capacity	5 persons
Maximum load capacity	710 kg
Weight without engine	650 kg
Deadrise at transom	14°
Deadrise midships	20°
Immersion	320 mm
Length	5.28 m
Width	2.28 m
Permissible engine power	90-150 h.p.
Fuel tank capacity	95 L
Transom height	508/635 mm
Hull material	AlMg 4/5 Mn (5083)
Hull thickness	3 mm